

Trade name: JACKODUR® perimeter adhesive foam

Product-no.:

Current version: 1.0 issued on 23.02.2017

Replaced version: -

Region: EN

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier:

Product name : JACKODUR® perimeter adhesive foam
 Produkttyp REACH : Mixture

1.2 Relevant identified uses of the substance or mixture and uses advised against:

1.2.1 Relevant identified uses

polyurethane

1.2.2 Uses advised against

No uses advised against known

1.3 Details of the supplier of the safety data sheet:

Supplier of the safety data sheet

JACKON Insulation GmbH
 Ritzlebener Straße 1
 D-39619 Arendsee
 Tel. +49 (0) 39036 / 960-0
 Fax +49 (0) 39036 / 960-290
 info@jackodur.com

1.4 Emergency telephone number:

Tel. +49 (0) 39036 / 960-0 (Telephone advice: English, French, German, Dutch)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture:

2.1.1 Classification according to Regulation EC No 1272/2008

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Aerosol	Category 1	H222: Extremely flammable aerosol.
Aerosol	Category 1	H229: Pressurised container: May burst if heated.
Carc.	Category 2	H351: Suspected of causing cancer.
Acute Tox.	Category 4	H332: Harmful if inhaled.
STOT RE	Category 2	H373: May cause damage to organs through prolonged or repeated exposure if inhaled.
Eye Irrit.	Category 2	H319: Causes serious eye irritation.
STOT SE	Category 3	H335: May cause respiratory irritation.
Skin Irrit.	Category 2	H315: Causes skin irritation.
Resp. Sens.	Category 1	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Sens.	Category 1	H317: May cause an allergic skin reaction.

EC-SAFETY DATA SHEET

Trade name: JACKODUR® perimeter adhesive foam

Product-no.:

Current version: 1.0 issued on 23.02.2017

Replaced version: -

Region: EN

2.1.2 Classification according to Directive 67/548/EEC-1999/45/EC

Classified as dangerous in accordance with the criteria of Directives 67/548/EEC and 1999/45/EC

Carc. Cat. 3; R40 - Limited evidence of a carcinogenic effect

F+; R12 - Extremely flammable.

Xn; R20 - 48/20 - Harmful by inhalation. Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Xi; R36/37/38 - Irritating to eyes, respiratory system and skin.

R42/43 - May cause sensitisation by inhalation and skin contact.

2.2 Label elements:

Labelling according to Regulation EC No 1272/2008 (CLP)

Drawn up according to the criteria of Regulation (EU) No 487/2013, 4th adaptation of Regulation (EC) No 1272/2008



Contains: polymethylene polyphenyl isocyanate.

Signal word	Danger
H-statements	
H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H351	Suspected of causing cancer.
H332	Harmful if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure if inhaled.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H315	Causes skin irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.

Signal word	Danger
P-statements	
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122°F.
P501	Dispose of contents/container in accordance with local/regional/national/international regulation.

Supplemental information

- Persons already sensitised to diisocyanates may develop allergic reactions when using this product.
- Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.
- This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

EC-SAFETY DATA SHEET

Trade name: JACKODUR® perimeter adhesive foam

Product-no.:

Current version: 1.0 issued on 23.02.2017

Replaced version: -

Region: EN

Labelling according to Directive 67/548/EEC-1999/45/EC (DSD/DPD)

Labels



Extremely flammable



Harmful

Contains: polymethylene polyphenyl isocyanate.

Signal word	Danger
R-phrases	
20	Harmful by inhalation
36 / 37 / 38	Irritating to eyes, respiratory system and skin
40	Limited evidence of a carcinogenic effect
42/43	May cause sensitisation by inhalation and skin contact
48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation

Signal word	Danger
S-phrases	
02	Keep out of the reach of children
16	Keep away from sources of ignition - No smoking
23	Do not breathe spray
36/37	Wear suitable protective clothing and gloves
45	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible)
51	Use only in well-ventilated areas
(63)	(In case of accident by inhalation: remove casualty to fresh air and keep at rest)

Additional recommendations

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C.

Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

Contains isocyanates. See information supplied by the manufacturer.

- Persons already sensitised to diisocyanates may develop allergic reactions when using this product.
- Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.
- This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

2.3 Other hazards:

CLP

May be ignited by sparks

Gas/vapour spreads at floor level: ignition hazard

Aerosol may explode under the effect of heat

EC-SAFETY DATA SHEET



Trade name: JACKODUR® perimeter adhesive foam

Product-no.:

Current version: 1.0 issued on 23.02.2017

Replaced version: -

Region: EN

DSD / DPD

May be ignited by sparks

Gas/vapour spreads at floor level: ignition hazard

Aerosol may explode under the effect of heat

SECTION 3: Composition/information on ingredients

3.1 Substances:

Not applicable

3.2 Mixtures:

Name REACH Registration No.	CAS No. EC No.	Conc. (C)	Classification according to DSD/DPD	Classification according to CLP	Note	Remark
tris(2-chloro-1-methylethyl) phosphate 01-2119447716-31	13674-84-5 237-158-7	1%<C<25%	Xn; R22	Acute Tox. 4; H302	(1)(10)	Constituent
polymethylene polyphenyl isocyanate	9016-87-9	C>25%	Carc. Cat. 3; R40 Xn; R20 - 48/20 Xi; R36/37/38 R42/43	Carc. 2; H351 Acute Tox. 4; H332 STOT RE 2; H373 Eye Irrit. 2; H319 STOT SE 3; H335 Skin Irrit. 2; H315 Resp. Sens. 1; H334 Skin Sens. 1; H317	(1)(2)(10)	Polymer
propane 01-2119486944-21	74-98-6 200-827-9	1%<C<10%	F+; R12	Flam. Gas 1; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant
isobutane 01-2119485395-27	75-28-5 200-857-2	1%<C<10%	F+; R12	Flam. Gas 1; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant
Ddimethyl ether 01-2119472128-37	115-10-6 204-065-8	1%<C<10%	F+; R12	Flam. Gas 1; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant
(1,3-butadiene, conc<0.1%)						

(1) For R-phrases and H-statements in full: see heading 16

(2) Substance with a Community workplace exposure limit

(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

SECTION 4: First aid measures

4.1 Description of first aid measures:

General:

GENERAL. Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with laboured breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up).

Trade name: JACKODUR® perimeter adhesive foam

Product-no.:

Current version: 1.0 issued on 23.02.2017

Replaced version: -

Region: EN

Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital.

After inhalation:

Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

After skin contact:

Wash immediately with lots of water. Take victim to a doctor if irritation persists.

After eye contact:

Rinse immediately with plenty of water. Do not apply neutralizing agents. Take victim to an ophthalmologist if irritation persists.

After ingestion:

Rinse mouth with water. Immediately after ingestion: give lots of water to drink. Do not induce vomiting. Consult a doctor/medical service if you feel unwell.

4.2 Most important symptoms and effects, both acute and delayed:

4.2.1 Acute symptoms

After inhalation:

Dry/sore throat. Coughing. Irritation of the respiratory tract. Irritation of the nasal mucous membranes. Runny nose. FOLLOWING SYMPTOMS MAY APPEAR LATER: Possible inflammation of the respiratory tract. Risk of lung oedema. Respiratory difficulties.

After skin contact:

Tingling/irritation of the skin.

After eye contact:

Irritation of the eye tissue. Lacrimation.

After ingestion:

Not applicable.

4.2.2 Delayed symptoms

No effects known.

4.3 Indication of any immediate medical attention and special treatment needed:

If applicable and available it will be listed below.

Trade name: JACKODUR® perimeter adhesive foam

Product-no.:

Current version: 1.0 issued on 23.02.2017

Replaced version: -

Region: EN

SECTION 5: Firefighting measures

5.1 Extinguishing media:

5.1.1 Suitable extinguishing media:

Quantities of water. Polyvalent foam. BC powder. Carbon dioxide.

5.1.2 Unsuitable extinguishing media:

No unsuitable extinguishing media known.

5.2 Special hazards arising from the substance or mixture:

On burning: release of toxic and corrosive gases/vapours (phosphorus oxides, nitrous vapours, hydrogen chloride, carbon monoxide - carbon dioxide). May polymerize on exposure to temperature rise. On heating: release of toxic/combustible gases/vapours (hydrogen cyanide).

5.3 Advice for firefighters:

5.3.1 Instructions:

If exposed to fire cool the closed containers by spraying with water. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistent risk of physical explosion. Dilute toxic gases with water spray.

5.3.2 Special protective equipment for fire-fighters:

Gloves. Protective goggles. Head/neck protection. Protective clothing. Heat/fire exposure: compressed air/oxygen apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment.

6.1.1 Protective equipment for non-emergency personnel

See heading 8.2

6.1.2 Protective equipment for emergency responders

Gloves. Protective goggles. Head/neck protection. Protective clothing.

Suitable protective clothing

See heading 8.2

6.2 Environmental precautions:

Dam up the solid spill. Use appropriate containment to avoid environmental contamination.

Trade name: JACKODUR® perimeter adhesive foam

Product-no.:

Current version: 1.0 issued on 23.02.2017

Replaced version: -

Region: EN

6.3 Methods and material for containment and cleaning up:

Allow product to solidify and remove it by mechanical means. Carefully collect the spill/leftovers. Clean (treat) contaminated surfaces with acetone. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

6.4 Reference to other sections:

See heading 13.

SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1 Precautions for safe handling:

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Observe very strict hygiene - avoid contact. Remove contaminated clothing immediately.

7.2 Conditions for safe storage, including any incompatibilities:

7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Store in a cool area. Keep out of direct sunlight. Ventilation at floor level. Fireproof storeroom. Unauthorized persons are not admitted. Meet the legal requirements. Max. storage time: 1 year(s).

7.2.2 Keep away from:

Heat sources, ignition sources, (strong) acids, (strong) bases, amines.

7.2.3 Suitable packaging material:

Aerosol.

7.2.4 Non suitable packaging material:

No data available

7.3 Specific end use(s):

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

Trade name: JACKODUR® perimeter adhesive foam

Product-no.:

Current version: 1.0 issued on 23.02.2017

Replaced version: -

Region: EN

SECTION 8: Exposure controls/personal protection

8.1 Control parameters:

8.1.1 Occupational exposure

a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

The Netherlands

Dimethylether	Time-weighted average exposure limit 8 h	496 ppm	Public occupational exposure limit value
	Time-weighted average exposure limit 8 h	950 mg/m ³	Public occupational exposure limit value
	Short time value	783 ppm	Public occupational exposure limit value
	Short time value	1500 mg/m ³	Public occupational exposure limit value

EU

Dimethylether	Time-weighted average exposure limit 8 h	1000 ppm	Indicative occupational exposure limit value
	Time-weighted average exposure limit 8 h	1920 mg/m ³	Indicative occupational exposure limit value

Belgien

Hydrocarbures aliphatiques sous forme gazeuse : (Alcanes C1-C4)	Time-weighted average exposure limit 8 h	1000 ppm	
Oxyde de diméthyle	Time-weighted average exposure limit 8 h	1000 ppm	
	Short time value	1920 mg/m ³	

USA

Butane, all isomers	Time-weighted average exposure limit 8 h	1000 ppm	TLV - Adopted Value
---------------------	--	----------	---------------------

Deutschland

Dimethylether	Time-weighted average exposure limit 8 h	1000 ppm	TRGS 900
	Time-weighted average exposure limit 8 h	1900 mg/m ³	TRGS 900

EC-SAFETY DATA SHEET



Trade name: JACKODUR® perimeter adhesive foam

Product-no.:

Current version: 1.0 issued on 23.02.2017

Replaced version: -

Region: EN

Isobutan	Time-weighted average exposure limit 8 h	1000 ppm	TRGS 900
	Time-weighted average exposure limit 8 h	2400 mg/m ³	TRGS 900
pMDI (als MDI berechnet)	Time-weighted average exposure limit 8 h	0.05 mg/m ³	TRGS 900
Propan	Time-weighted average exposure limit 8 h	1000 ppm	TRGS 900
	Time-weighted average exposure limit 8 h	1800 mg/ m ³	TRGS 900

Frankreich

Oxyde de diméthyle	Time-weighted average exposure limit 8 h	1000 ppm	VRI: Valeur réglementaire indicative
	Time-weighted average exposure limit 8 h	1920 mg/ m ³	VRI: Valeur réglementaire indicative

UK

Dimethyl ether	Zeitlich gewichteter durchschnittlicher ExpositionsgrenzValue 8h	400 ppm	Workplace exposure limit (EH40/2005)
	Time-weighted average exposure limit 8 h	766 mg/m ³	Workplace exposure limit (EH40/2005)
	Short time value	500ppm	Workplace exposure limit (EH40/2005)
	Short time value	958 mg/m ³	Workplace exposure limit (EH40/2005)
Isocyanates, all (as -NCO) Except methylisocyanate	Time-weighted average exposure limit 8 h	0.02 mg/ m ³	Workplace exposure limit (EH40/2005)
	Short time value	0.07 mg/ m ³	Workplace exposure limit (EH40/2005)

b) National biological limit values

If limit values are applicable and available these will be listed below.

8.1.2 Sampling methods

Product name	Test	Number
Methylene Bisphenyl Isocyanate (MDI)	OSHA	47

8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

EC-SAFETY DATA SHEET



Trade name: JACKODUR® perimeter adhesive foam

Product-no.:

Current version: 1.0 issued on 23.02.2017

Replaced version: -

Region: EN

8.1.4 DNEL/PNEC-values

DNEL - Workers

tris(2-chloro-1-methylethyl) phosphate

Effect level (DNEL/DMEL)	Typ	Value	Bemerkung
DNEL	Acute systemic effects dermal	0.528 mg/kg bw/day	
	Acute systemic effects inhalation	0.93 mg/m ³	
	Long-term systemic effects dermal	0.528 mg/kg bw/day	
	Long-term systemic effects inhalation	0.93 mg/m ³	

DNEL - General population

tris(2-chloro-1-methylethyl) phosphate

Effect level (DNEL/DMEL)	Typ	Value	Bemerkung
DNEL	Acute systemic effects dermal	0.264 mg/kg bw/day	
	Acute systemic effects inhalation	0.23 mg/m ³	
	Acute -systemic effects oral	0.33 mg/kg bw/day	
	Long-term systemic effects dermal	0.264 mg/kg bw/day	
	Long-term systemic effects inhalation	0.23 mg/m ³	
	Long-term systemic effects oral	0.33 mg/kg bw/day	

8.1.5 Control banding

If applicable and available it will be listed below.

8.2 Exposure controls:

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

8.2.1 Appropriate engineering controls

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Measure the concentration in the air regularly.

8.2.2 Individual protection measures, such as personal protective equipment

Observe very strict hygiene - avoid contact. Do not eat, drink or smoke during work.

a) Respiratory protection:

Wear gas mask with filter type A if conc. in air > exposure limit.

b) Hand protection:

Gloves.

Materials	Breakthrough time	Thickness
LDPE (Low Density Poly Ethylene)	10 minutes	0.025 mm

- materials (good resistance)

LDPE (Low Density Poly Ethylene).

EC-SAFETY DATA SHEET



Trade name: JACKODUR® perimeter adhesive foam

Product-no.:

Current version: 1.0 issued on 23.02.2017

Replaced version: -

Region: EN

c) Eye protection:

Protective goggles.

d) Skin protection:

Head/neck protection. Protective clothing.

8.2.3 Environmental exposure controls:

See headings 6.2, 6.3 and 13

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties:

Physical form	Aerosol
Odour	Characteristic odour
Odour threshold	No data available
Colour	Variable in colour, depending on the composition
Particle size	No data available
Explosion limits	No data available
Flammability	Extremely flammable aerosol
Log Kow	Not applicable (mixture)
Dynamic viscosity	No data available
Kinematic viscosity	No data available
Melting point	No data available
Boiling point	No data available
Flash point	Not applicable
Evaporation rate	No data available
Relative vapour density	> 1
Vapour pressure	No data available
Solubility	water ; insoluble organic solvents ; soluble
Relative density	0.95 ; 20 °C
Decomposition temperature	No data available
Auto-ignition temperature	No data available
Explosive properties	No chemical group associated with oxidising properties
Oxidising properties	No chemical group associated with oxidising properties
pH	No data available

Physical hazards

Flammable aerosol

9.2 Other information:

Surface tension	No data available
Absolute density	950 kg/m ³ ; 20 °C

SECTION 10: Stability and reactivity

10.1 Reactivity:

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard. No data available.

Trade name: JACKODUR® perimeter adhesive foam

Product-no.:

Current version: 1.0 issued on 23.02.2017

Replaced version: -

Region: EN

10.2 Chemical stability:

Stable under normal conditions.

10.3 Possibility of hazardous reactions:

May polymerize with many compounds e.g.: (strong) bases and amines. Reacts violently with (some) acids/bases.

10.4 Conditions to avoid:

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks.

10.5 Incompatible materials:

(strong) acids, (strong) bases, amines.

10.6 Hazardous decomposition products:

On heating: release of toxic/combustible gases/vapours (hydrogen cyanide). On burning: release of toxic and corrosive gases/vapours (phosphorus oxides, nitrous vapours, hydrogen chloride, carbon monoxide - carbon dioxide).

SECTION 11: Toxicological information

11.1 Information on toxicological effects:

11.1.1 Test results

Acute toxicity

JACKODUR® perimeter adhesive foam

No (test)data on the mixture available

tris(2-chloro-1-methylethyl) phosphate

Route of exposure	Parameter	Method	Value	Exposure time	Species	Gender	Value determination
Oral	LD50	Equivalent to OECD 401	1011-1824 mg/kg bw		Rat	Male/female	Experimental value
Dermal	LD50	OECD 402	> 2000 mg/kg bw	24 h	Rabbit	Male/female	Experimental value
Inhalation (Aerosol)	LC50	Equivalent to OECD 403	> 5 mg/l Luft	4 h	Rat	Male/female	Weight of evidence

polymethylene polyphenyl isocyanate

Route of exposure	Parameter	Method	Value	Exposure time	Species	Gender	Value determination
Oral	LD50		> 10000 mg/kg		Rat		Literature study
Dermal	LD50		> 5000 mg/kg		Rabbit		Literature study
Inhalation (vapours)	LD50		10-20 mg/l	4 h	Rat		Literature study

Classification is based on the relevant ingredients

EC-SAFETY DATA SHEET



Trade name: JACKODUR® perimeter adhesive foam

Product-no.:

Current version: 1.0 issued on 23.02.2017

Replaced version: -

Region: EN

Conclusion

Harmful if inhaled.

Low acute toxicity by the dermal route

Low acute toxicity by the oral route

Corrosion/irritation

JACKODUR® perimeter adhesive foam

No (test)data on the mixture available

tris(2-chloro-1-methylethyl) phosphate

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination
Eye	Not irritating	Equivalent to OECD 405	72 h	24; 48; 72 hours	Rabbit	Experimental value
Skin	Not irritating	OECD 404	4 h		Rabbit	Experimental value

polymethylene polyphenyl isocyanate

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination
Eye	Irritating					Literature study
Skin	Irritating					Literature study
Inhalation	Irritating					Literature study

Classification is based on the relevant ingredients

Conclusion

Causes skin irritation.

Causes serious eye irritation.

May cause respiratory irritation.

Specific target organ toxicity, single exposure: classified as irritant to respiratory organs

EC-SAFETY DATA SHEET



Trade name: JACKODUR® perimeter adhesive foam

Product-no.:

Current version: 1.0 issued on 23.02.2017

Replaced version: -

Region: EN

Respiratory or skin sensitisation

JACKODUR® perimeter adhesive foam

No (test)data on the mixture available

tris(2-chloro-1-methylethyl) phosphate

Route of exposure	Result	Method	Exposure time	Species	Gender	Value determination
Skin	Not sensitizing	OECD 429		Mouse		Experimental value

Route of exposure	Result	Method	Exposure time	Species	Gender	Value determination
Skin	Sensitizing					Literature study
Inhalation	Sensitizing					Literature study

Classification is based on the relevant ingredients

Conclusion

May cause an allergic skin reaction.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Specific target organ toxicity

JACKODUR® perimeter adhesive foam.

No (test)data on the mixture available

tris(2-chloro-1-methylethyl) phosphate

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Gender	Value determination
Oral	LOAEL	Equivalent to OECD 408	800 ppm	Liver	Weight gain	13 weeks (daily)	Rat	Male	Experimental value
Oral	NOAEL	Equivalent to OECD 408	2500 ppm		No effect	13 weeks (daily)	Rat	Female	Experimental value

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Gender	Value determination
Inhalation			STOT RE Kat.2						Literature study

Classification is based on the relevant ingredients

Conclusion

May cause damage to organs through prolonged or repeated exposure if inhaled.

Low sub-chronic toxicity by the dermal route

Low sub-chronic toxicity by the oral route

Mutagenicity (in vitro)

JACKODUR® perimeter adhesive foam

No (test)data on the mixture available

tris(2-chloro-1-methylethyl) phosphate

EC-SAFETY DATA SHEET



Trade name: JACKODUR® perimeter adhesive foam

Product-no.:

Current version: 1.0 issued on 23.02.2017

Replaced version: -

Region: EN

Result	Method	Test substrate	Effect	Value determination
Negative		Chinese hamster lung fibroblasts	No effect	Weight of evidence
Negative	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Weight of evidence
Negative	Equivalent to OECD 476	Mouse (lymphoma L5178Y cells)	No effect	Weight of evidence

Mutagenicity (in vivo)

JACKODUR® perimeter adhesive foam

No (test)data on the mixture available

tris(2-chloro-1-methylethyl) phosphate

Result	Method	Exposure time	Test substrate	Gender	Organ	Value determination
Negative	Equivalent to OECD 475		Rat	Male		Weight of evidence

Carcinogenicity

JACKODUR® perimeter adhesive foam

No (test)data on the mixture available

polymethylene polyphenyl isocyanate

Route of exposure	Parameter	Method	Value	Exposure time	Species	Gender	Value determination	Organ	Effect
Inhalation (aerosol)			category 2		Rat		Literature study		Neoplastic effects

Reproductive toxicity

JACKODUR® perimeter adhesive foam

No (test)data on the mixture available

Tris(2-chlor-1-methylethyl)phosphat

	Parameter	Method	Value	Exposure time	Species	Gender	Effect	Organ	Value determination
Developmental toxicity	LOAEL (P)	OECD 416	99 mg/kg bw	>10 weeks (daily)	Rat	Female	Body weight, organ weight, food consumption	Female reproductive organ	Experimental value
	NOAEL (P)	OECD 416	85 mg/kg bw	>10 weeks (daily)	Rat	Male	No effect		Experimental value
	NOAEL	Equivalent to OECD 414	1000 mg/kg bw	70 day(s)	Rat	Female	No effect		Experimental value

Classification is based on the relevant ingredients.

Conclusion CMR

Suspected of causing cancer.

Not classified for mutagenic or genotoxic toxicity

Not classified for reprotoxic or developmental toxicity

Toxicity other effects

JACKODUR® perimeter adhesive foam

No (test)data on the mixture available

EC-SAFETY DATA SHEET



Trade name: JACKODUR® perimeter adhesive foam

Product-no.:

Current version: 1.0 issued on 23.02.2017

Replaced version: -

Region: EN

Chronic effects from short and long-term exposure

JACKODUR® perimeter adhesive foam

ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Feeling of weakness. Itching. Skin rash/inflammation. May stain the skin.

Dry skin. Coughing. Possible inflammation of the respiratory tract. Respiratory difficulties.

SECTION 12: Ecological information

12.1 Toxicity:

JACKODUR® perimeter adhesive foam

No (test)data on the mixture available

tris(2-chloro-1-methylethyl) phosphate

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50		56.2 mg/l	96 h	Brachydanio rerio	Static system	Fresh water	Experimental value; GLP
Acute toxicity invertebrates	EC50	OECD 202	65 - 335 mg/l	48 h	Daphnia magna			Experimental value; GLP
Toxicity algae and other aquatic plants	EC50	OECD 201	73 mg/l	96 h	Selenastrum capricornutum			Experimental value; Growth rate

polymethylene polyphenyl isocyanate

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity other aquatic organisms	LC50		>1000 mg/l	96 h			Fresh water	Literaturstudie
Toxicity aquatic microorganisms	EC50	OECD 209	>100 mg/l		Belebtschlamm			Literaturstudie

Classification of the mixture is based on the relevant ingredients of the mixture

Conclusion

Contains non readily biodegradable component(s)

12.2 Persistence and degradability:

tris(2-chloro-1-methylethyl) phosphate

Biodegradation water

Method	Value	Duration	Value determination
OECD 301E: Modified OECD Screening Test	14%	28 day(s)	Experimental value
OECD 301C: Modified MITI Test (I)	0%	28 day(s)	Experimental value

polymethylene polyphenyl isocyanate

EC-SAFETY DATA SHEET



Trade name: JACKODUR® perimeter adhesive foam

Product-no.:

Current version: 1.0 issued on 23.02.2017

Replaced version: -

Region: EN

Biodegradation water

Method	Value	Duration	Value determination
OECD 302C: Inherent Biodegradability: Modified MITI Test (II)	< 60 %		Experimental value

Konklusion

Enthält biologisch nicht leicht abbaubare Komponente(n).

12.3 Bioaccumulative potential:

JACKODUR® perimeter adhesive foam

Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

Tris(2-chlor-1-methylethyl)phosphat

BCF Fische

Parameter	Method	Value	Duration	Species	Value determination
BCF		0.8 - 4.6		Cyprinus carpio	Experimental value

Log Know

Method	Remark	Value	Temperature	Value determination
		2.59		Experimental value

polymethylene polyphenyl isocyanate

BCF Fische

Parameter	Method	Value	Duration	Species	Value determination
BCF		1		Pisces	rature study

Log Know

Method	Remark	Value	Temperature	Value determination
	No data available			

Conclusion

No bioaccumulation data available

Trade name: JACKODUR® perimeter adhesive foam

Product-no.:

Current version: 1.0 issued on 23.02.2017

Replaced version: -

Region: EN

12.4 Mobility in soil:

No (test) data on mobility of the components available

12.5 Results of PBT and vPvB assessment:

Due to insufficient data no statement can be made whether the component(s) fulfill(s) the criteria of PBT and vPvB according to Annex XIII of Regulation (EC) No 1907/2006.

12.6 Other adverse effects:

JACKODUR® perimeter adhesive foam

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

13.1 Waste treatment methods:

13.1.1 Provisions relating to waste

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

08 04 09* (wastes from MFSU of adhesives and sealants (including waterproofing products): waste adhesives and sealants containing organic solvents or other dangerous substances). Depen

13.1.2 Disposal methods

Remove waste in accordance with local and/or national regulations. Specific treatment. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Do not discharge into drains or the environment.

13.1.3 Packaging/Container

Waste material code packaging (Directive 2008/98/EC).

15 01 10* (packaging containing residues of or contaminated by dangerous substances).

EC-SAFETY DATA SHEET



Trade name: JACKODUR® perimeter adhesive foam

Product-no.:

Current version: 1.0 issued on 23.02.2017

Replaced version: -

Region: EN

SECTION 14: Transport information

Road (ADR)

14.1 UN number:

UN number	1950
-----------	------

14.2 UN proper shipping name:

Proper shipping name	Aerosols
----------------------	----------

14.3 Transport hazard class(es):

Hazard identification number	
Class	2
Classification code	5F

14.4 Packing group:

Packing group:	
Labels	2.1

14.5 Environmental hazards:

Environmentally hazardous substance mark	no
--	----

14.6 Special precautions for user:

Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

Rail (RID)

14.1 UN number:

UN number	1950
-----------	------

EC-SAFETY DATA SHEET



Trade name: JACKODUR® perimeter adhesive foam

Product-no.:

Current version: 1.0 issued on 23.02.2017

Replaced version: -

Region: EN

14.2 UN proper shipping name:

Proper shipping name	Aerosols
----------------------	----------

14.3 Transport hazard class(es):

Hazard identification number	23
Class	2
Classification code	5F

14.4 Packing group:

Packing group	
Labels	2.1

14.5 Environmental hazards:

Environmentally hazardous substance mark	no
--	----

14.6 Special precautions for user:

Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

Inland waterways (ADN)

14.1 UN number:

UN number	1950
-----------	------

14.2 UN proper shipping name:

Proper shipping name	Aerosols
----------------------	----------

EC-SAFETY DATA SHEET



Trade name: JACKODUR® perimeter adhesive foam

Product-no.:

Current version: 1.0 issued on 23.02.2017

Replaced version: -

Region: EN

14.3 Transport hazard class(es):

Class	2
Classification code	5F

14.4 Packing group:

Packing group	
Labels	2.1

14.5 Environmental hazards:

Environmentally hazardous substance mark	no
--	----

14.6 Special precautions for user:

Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

Sea (IMDG/IMSBC)

14.1 UN number:

UN number	1950
-----------	------

14.2 UN proper shipping name:

Proper shipping name	Aerosols
----------------------	----------

14.3 Transport hazard class(es):

Class	2.1
-------	-----

EC-SAFETY DATA SHEET



Trade name: JACKODUR® perimeter adhesive foam

Product-no.:

Current version: 1.0 issued on 23.02.2017

Replaced version: -

Region: EN

14.4 Packing group:

Packing group	
Labels	2.1

14.5 Environmental hazards:

Marine pollutant	-
Environmentally hazardous substance mark	no

14.6 Special precautions for user:

Special provisions	63
Special provisions	190
Special provisions	277
Special provisions	327
Special provisions	344
Special provisions	959
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Annex II of MARPOL 73/78 Not

Annex II of MARPOL 73/78	Nicht anwendbar
--------------------------	-----------------

Air (ICAO-TI/IATA-DGR)

14.1 UN number:

UN number	1950
-----------	------

14.2 UN proper shipping name:

Proper shipping name	Aerosols, flammable
----------------------	---------------------

14.3 Transport hazard class(es):

Class	2.1
-------	-----

EC-SAFETY DATA SHEET



Trade name: JACKODUR® perimeter adhesive foam

Product-no.:

Current version: 1.0 issued on 23.02.2017

Replaced version: -

Region: EN

14.4 Packing group:

Packing group	
Labels	2.1

14.5 Environmental hazards:

Environmentally hazardous substance mark	no
--	----

14.6 Special precautions for user:

Special provisions	A145
Special provisions	A167
Special provisions	A802
Special provisions	625
Passenger and cargo transport: limited quantities: maximum net quantity per packaging	30 kg G

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

European legislation:

VOC content Directive 2010/75/EU

FVOC content	Remark
20 %	

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

EC-SAFETY DATA SHEET



Trade name: JACKODUR® perimeter adhesive foam

Product-no.:

Current version: 1.0 issued on 23.02.2017

Replaced version: -

Region: EN

	Classification of the substance, of the group of substances or of the mixture	Conditions of restriction
<ul style="list-style-type: none"> · tris(2-chloro-1-methylethyl) phosphate · polymethylene polyphenyl isocyanate 	<p>Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC)</p> <p>No 1272/2008:</p> <p>(a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F;</p> <p>(b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10;</p> <p>(c) hazard class 4.1;</p> <p>(d) hazard class 5.1.</p>	<p>1. Shall not be used in:</p> <ul style="list-style-type: none"> — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even with ornamental aspects, <p>2. Articles not complying with paragraph 1 shall not be placed on the market.</p> <p>3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:</p> <ul style="list-style-type: none"> — can be used as fuel in decorative oil lamps for supply to the general public, and, — present an aspiration hazard and are labelled with R65 or H304, <p>4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).</p> <p>5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:</p> <p>a) lamp oils, labelled with R65 or H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life-threatening lung damage";</p> <p>b) grill lighter fluids, labelled with R65 or H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage";</p> <p>c) lamp oils and grill lighters, labelled with R65 or H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.6. No later than 1 June 2014, the Commission shall request the European Chemicals Agency to prepare a dossier, in accordance with Article 69 of the present Regulation with a view to ban, if appropriate, grill lighter fluids and fuel for decorative lamps, labelled R65 or H304, intended for supply to the general public.7. Natural or legal persons placing on the market for the first time lamp oils and grill lighter fluids, labelled with R65 or H304, shall by 1 December 2011, and annually thereafter, provide data on alternatives to lamp oils and grill lighter fluids labelled R65 or H304 to the competent authority in the Member State concerned. Member States shall make those data available to the Commission.'</p>

EC-SAFETY DATA SHEET



Trade name: JACKODUR® perimeter adhesive foam

Product-no.:

Current version: 1.0 issued on 23.02.2017

Replaced version: -

Region: EN

<ul style="list-style-type: none"> polymethylene polyphenyl isocyanate 	<p>Methylenediphenyl diisocyanate (MDI) including the following specific isomers: 4,4'-Methylenediphenyl diisocyanate; 2,4'-Methylenediphenyl diisocyanate; 2,2'-Methylenediphenyl diisocyanate</p>	<p>1. Shall not be placed on the market after 27 December 2010, as a constituent of mixtures in concentrations equal to or greater than 0,1 % by weight of MDI for supply to the general public, unless suppliers shall ensure before the placing on the market that the packaging:</p> <p>(a) contains protective gloves which comply with the requirements of Council Directive 89/686/EEC;</p> <p>(b) is marked visibly, legibly and indelibly as follows, and without prejudice to other Community legislation concerning the classification, packaging and labelling of substances and mixtures:</p> <p>“— Persons already sensitised to diisocyanates may develop allergic reactions when using this product.</p> <p>— Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.</p> <p>— This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.2. By way of derogation, paragraph 1(a) shall not apply to hot melt adhesives.</p>
---	---	---

Reference legislation

See column 1: 3.

See column 1: 40.

See column 1: 56.

Recommendations REACH annex XVII

- Persons already sensitised to diisocyanates may develop allergic reactions when using this product.

National legislation The Netherlands

JACKODUR® perimeter adhesive foam

Waste identification (the Netherlands)	LWCA (the Netherlands): KGA category 06
Waterbezwaarlijkheid	8

National legislation Germany

JACKODUR® perimeter adhesive foam

WGK	1; Classification water polluting based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS) of 27 July 2005 (Anhang 4)
-----	---

polymethylene polyphenyl isocyanate

EC-SAFETY DATA SHEET



Trade name: JACKODUR® perimeter adhesive foam

Product-no.:

Current version: 1.0 issued on 23.02.2017

Replaced version: -

Region: EN

TRGS905 - Krebserzeugend	3
TRGS905 - Erbgutverändernd	-
TRGS905 - Fruchtbarkeitsgefährdend	-
TRGS905 - Fruchtschädigend	-
MAK - Krebserzeugend Kategorie	4
Schwangerschaft Gruppe	C
MAK 8-Stunden-MittelValue mg/m ³	„polymeres MDI“ (einatembare Fraktion); 0.05 mg/m ³ ; gemessen als einatembare Fraktion (vgl. Abschn. Vd) S. 191)

National legislation France

JACKODUR® perimeter adhesive foam

No data available

Nationale Gesetzgebung Belgien

JACKODUR® perimeter adhesive foam

No data available

15.2 Chemical safety assessment:

No chemical safety assessment is required.

SECTION 16: Other information

Full text of any R-phrases referred to under headings 2 and 3:

R20 Harmful by inhalation

R22 Harmful if swallowed

R36/37/38 Irritating to eyes, respiratory system and skin

R40 Limited evidence of a carcinogenic effect

R42/43 May cause sensitisation by inhalation and skin contact

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation

Full text of any H-statements referred to under headings 2 and 3:

H220 Extremely flammable gas.

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

EC-SAFETY DATA SHEET



Trade name: JACKODUR® perimeter adhesive foam

Product-no.:

Current version: 1.0 issued on 23.02.2017

Replaced version: -

Region: EN

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

(*) = INTERNAL CLASSIFICATION BY BIG

PBT-substances = persistent, bioaccumulative and toxic substances

DSD Dangerous Substance Directive

DPD Dangerous Preparation Directive

CLP (EU-GHS) Classification, labelling and packaging (Globally Harmonised System in Europe)

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Old versions must be destroyed. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided

and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.